



AUTENTICO® Undercoat

Product Description:

Autentico Undercoat is a high quality and solvent-free for interior use. This grey-based Undercoat is perfect preparation for: general adherence, walls and ceilings being painted with Autentico Velvet or Venice and preparing furniture prone to bleed-through and blocking stains before painting with Autentico Vintage or Venice.

Location:

Interior.

Suggested Applications:

Can be applied to most suitably prepared surfaces; Interior wood, walls, brickwork, PVC and more.

Preparation:

NEW/UNPAINTED SUBSTRATES:

Make sure substrates are dry, clean and stable as well as free from dirt, grease, mould or any other loose materials. Cleaning with Autentico Omniclean is recommended.

If applying to fresh plaster, do not proceed with application until all plaster has thoroughly set and dried.

PREVIOUSLY PAINTED AND OTHER SUBSTRATES:

Autentico® Undercoat should only be applied to dry, clean and stable surfaces it will adhere directly over previously painted walls, ceilings and floors. When painting over glossy surfaces or plastics, sanding to remove gloss and create a “key” for adherence is paramount.

When applying to metal surface, use an appropriate primer developed to prevent metal from rusting.

Application:

Stir well prior to use. Apply two thin coats or as required with brush or short pile roller. If using to prevent bleed-through of knots, coat the entire surface not just the knots.

Drying Times:

Touch dry in 30 minutes. Allow minimum of 4-hour drying time between coats. (Drying times may vary dependent on temperature and surface profile and porosity) The minimum temperature at which Autentico Undercoat will form a film is 10°C.

Coverage:

Covers approximately between 8-13m² per 1 litre depending on surface profile and porosity.

Packaging:

Autentico® Undercoat is available in 1 litre.

Limitations:

Autentico Undercoat does not prevent rust when applying to a metal substrate. Use Autentico Metal Primer for that use. All Autentico products should not be applied in high humidity, below 5°C or above 30°C.

Storage:

Keep in a cool dry place, away from risk of frost. Do not store below 5°C or above 30°C.

Cleaning and Disposal:

Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

Environmental Information:

This product contains EU limit value for the VOC. EU target level for this product: 30g/L

Autentico® The Charm of Chalks uses only the finest quality, low odour and minimal environmental impact raw materials. Our manufacturing processes are zero waste and all paint formulations are designed for maximum performance with minimum impact on user health. ≈ 16 g/l Interior Matt walls and ceilings (Gloss <25%@60°C) : Value limits of the EU for this product (VOC2010) : 30 g/l. Contains chloromethylisothiazoloneon &

methylothiazolineon (3:1), bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate,
Hydroxyphenylbenzotriazol (mixture)

Health and Safety:

Ensure good ventilation. Keep out of reach of children. If in contact with eyes, rinse immediately with warm water consistently with eye lids open for at least 10 minutes. Keep in cool dry place away from risk of frost. Safety data sheets available upon request.

Manufacturers Details:

Unit 4, The Glenmore Centre
Moat Way
Ashford
Kent
TN24 0TL

01233878303

www.autentico-paint.com
enquiries@autentico-paint.com